Information Technology Disaster Recovery Plan (IT DRP)

Jordan Fflubes
Last Updated & Tested :
23/09/2025

RD DIGITAL

Introduction

This document details the policies and procedures of Recognise Design Limited in the event of a disruption to critical IT services or damage to IT equipment or data. These processes will enable us to:

Have assets you necessitate to the right level and within the right time frame.

Our mission is to ensure information system uptime, data integrity and availability, and business continuity.

RD DIGITAL

Purpose of policy

Corporate management has approved the following policy statement:

- The company will establish a formal disaster recovery plan (DRP).
- The company's each resources plans should cover essential and critical infrastructure elements, systems and networks, in accordance with key business activities.
- The DRP will be communicated to all employees who are involved with DRP and trained to execute it.
- The DRP will be tested at least annually to ensure that management and staff understand how it is to be executed.
- All staff must be made aware of the plans and their own respective roles.
- The DRP is to be kept current to take into account changing circumstances.

RD DIGITAL

Business impact analysis

This business impact analysis is to used when doing the planning and for the Risk Log.

The first section is about identifying critical IT systems and networks that a business including the business head of department must have in order identifying the business needs and priorities, including risks and data confidentiality.

Business Impact	Impact to the company	Impact if the company fails to meet this requirement
Finance	IT system B	Will stop invoicing customers and processing payments. Could be unable after 10 hours.
HR	IT system C	Inability to pay staff, manual procedures, unauthorised staff may be paid.
All business staff	Email system	Will impact communication with customers immediately after 4 hours.

RD DIGITAL

#SuccessStartsHere

Business process/systems	Business process/systems				
	Availability	RTO	RPO	Data integrity	Data confidentiality
IT system A	99.7%	4 h	15 min	Very high	Low
IT system B	99.9%	2 h	30 min	Very high	High
IT system C	99.9%	8H	24 h	Very high	Very high
Email system	99.9%	4 h	24 h	Very high	Medium

The Recovery Time Objective (RTO) is the time frame agreed upon as the maximum permissible, operational gaps after an IT infrastructure (including all IT resources) failure, before the business is severely impacted. The Recovery Point Objective (RPO) is the greatest tolerable period in which data might be lost from a IT service due to a major incident. The lower the business can bankup/restore/replicate solutions.

Note: RTO and RPO are different. Prioritization steps initial and isn't changed intentionally or unintentionally.

Note: Availability is the time demand that everyone. Much the metrics is not made available or disclosed intentionally or unintentionally to others.

RD DIGITAL

#SuccessStartsHere

Robustness analysis

Lists the individuals responsible for maintaining and updating the Plan and its tools. Have an extensive discussion about the responsibilities that is essential to the service holder.

Name	Description	Implementation date
Backup Technician assistant	Daily monitoring, new action for IT systems	Added to the IT: 01/07/2025
IPTV email system	Move the Mail for a Domain to Office 365 Migration with the Migration Tool	Discussion: 01/07/2025
Server end of back-date vision	Windows Server 2012 R2 will be supported by Microsoft until October 10, 2023.	Discussion: 01/07/2025

RD DIGITAL

#SuccessStartsHere

Recovery planning section

This part of the business continuity plan covers preparations to handle IT interruptions in an efficient way and reduce the impact on the business.

RD DIGITAL

#SuccessStartsHere

Key personal contact details

Name, Title	Contact option	Contact number
Jordan Fflubes	Work	07700123123
	Mobile	07700123123
	Home	07700123123
	Email address	jordanfflubes@recognisedesign.com
Abel Bourne	Work	n/a, 7526 Hotdesk
	Mobile	n/a, 7526 Hotdesk
	Home	Unknown
	Email address	Abel.bourne@recognisedesign.com

RD DIGITAL

#SuccessStartsHere

Prepared DR procedures

Depending on the incident, one or more of the following disaster recovery procedures may be activated.

DR plan for Ransomware

Scenario	Ransomware event and full activity, including accidental file encryption and data exfiltration
Possible causes	Malware
IT services and data at risk	Storage systems and backups
Impact	Lost or corrupted data
Prevention	• Identify potential weaknesses of our network and IT environment • Implement the use of IPS and IDS to monitor for all attacks and prevent

RD DIGITAL

#SuccessStartsHere

Prevention	• Employees that are critical IT services should have the maximum access • Employees should be trained on the DR plan • Implement a training and awareness plan for all the data owners (e.g. the C.E.O.) • Make a minimum of three copies of data. • Store two of the copies on different media. • Secure one copy of an encrypted file. • Ensure that all software, including operating systems, which will defend the impact of a data breach and vulnerability be recovery process. • Ensure that all software, including operating systems, which will defend the protection • Implement logs on all the devices that are critical to the business operation. • Implement a firewall to protect the network from unauthorized access. • Restrict other operating systems, antivirus, security, and backup software to save • Implement ongoing cybersecurity training for new and existing employees to identify phishing
Plan of action	• Disconnect all ransomware-affected systems from the network. • Identify the ransomware variant and assess the extent of the damage. • Locate your data back. In many cases local backup drives, if it isn't "networks" or share drives, will be safe from the ransomware. Check to see if this is the case. • Do not try to decrypt the data by yourself. Certified IT professionals have the tools and experience to do this safely. • Do not pay the ransom. There is no guarantee that you will get your data back if you pay the ransom. Additionally, you may encourage the attackers to target your business again in the future. • Identify the virus, malware, or ransomware that caused the attack. • Remove the virus, malware, or ransomware from the network. • Follow the instructions in details
Key contacts	• Jordan Fflubes • Abel Bourne
IT services and data at risk	Storage systems that support critical machines
Impact	Lost or corrupted data

RD DIGITAL

#SuccessStartsHere

DR plan for virtualised systems

Scenario	Data loss and failure in virtual systems
Possible causes	• Lack of free, Every second IT employee tasks the Risk to regularly document • Human error or sabotage • Overloading or work on an effective process after a data deletion has occurred • Hardware or software failure • Destruction, misuse, or theft of hardware • Software bugs or viruses • Natural disasters such as floods, fires, or earthquakes • Power outages
Plan of action	• Determine proper backup for all systems that contain critical functions. • Identify the most critical systems to be protected against the IPv4 data loss. • Document • Document testing procedures are an active and have an emergency data recovery plan in place. • Identify the most critical production system to protect against the IPv4 data loss. • Ensure that backups are stored in a secure location, preferably off-site, and that they are regularly tested to ensure they can be restored in the event of a disaster. • Develop a disaster recovery plan that outlines the steps to be taken in the event of a disaster, including who is responsible for each step and how to restore critical systems and data. • Implement redundancy and failover mechanisms to minimize downtime in the event of a hardware or software failure.
Key contacts	• Jordan Fflubes • Abel Bourne

RD DIGITAL

#SuccessStartsHere

DR plan for RAID-systems

Scenario	Data loss and failure in RAID systems
Possible causes	**Human error** • Accidentally deleted or overwrote a file • Accidentally formatted a drive or partition • Physically damaged a hard drive or other piece of hardware **Power issues** • Power outages can also affect the loss of power, causing data corruption. • Power surges can damage hardware components, leading to data loss. • Brownouts can cause intermittent power issues that can also result in data loss or corruption. **Hardware issues and failed rebuilds** • RAID controllers can fail, rendering the entire array inaccessible. • Failed rebuilds can occur when a new drive is added to the array, but the rebuild process is interrupted or fails. • Hardware incompatibility issues can also cause problems with the RAID array. **Natural disasters** • Fire, water, dirt, and other contaminants from natural disasters can destroy data. **Software issues** • Software bugs or glitches in the RAID software can also cause data loss.
IT services and data at risk	RAID systems
Impact	Lost or corrupted data

RD DIGITAL

#SuccessStartsHere

Plan of action	**Do not use CHKDSK** CHKDSK can be dangerous to run for drives on systems experiencing minor corruption. It can cause more harm than good by overwriting critical file system information. Instead, use a tool like Windows Server 2012 Update Rollup 2 (KB2869594) or later, which includes improvements to the CHKDSK utility. Therefore, data loss in RAID 0 is the most risk-free. Therefore, data loss in RAID 0 is the most risk-free. **Never replace a failed drive with a drive that was part of a previous RAID array** • Always use a new, unused drive. **If a drive is making unusual mechanical noises, turn it off immediately.** • Continuing to run a drive with mechanical issues can cause further damage and may make the data recovery job more difficult and expensive.

RD DIGITAL

#SuccessStartsHere

Plan of action	• Verify that no system administrators existing maintenance or software changes. • Label the drive with the system's name and the date it was removed from the RAID array. • If RAID system fails in the middle of a rebuild process, do not run the four rebuild attempts. • In certain rare situations, a RAID 0 array may fail to start after a reboot or power outage. This is usually due to a problem with the array's configuration or a corrupt repair strategy.
Key contacts	• Jordan Fflubes • Abel Bourne

RD DIGITAL

#SuccessStartsHere

DR plan for single HDD and SSD

Scenario	Data loss and failure of single drives
Possible causes	**Mechanical failure** • Physical damage to the platters or read/write head, spindle motor, or PCB. • Data loss occurring in mechanical failure. This could be due to a head crash and/or bad sectors. **Logical failure** • Data loss occurring logical loss can occur in several ways, or other files. Files may be experiencing a logical issue. This could be due to a bad partition or accidental deletion of data.
IT services and data at risk	Has data stored locally on a single drive
Impact	Lost data

RD DIGITAL

#SuccessStartsHere

Plan of action	**Power off** • Turn off the computer to the computer or storage device to prevent further damage to the drive. **Remove the drive** • Carefully remove the drive from the computer, taking care not to damage the drive or the surrounding components. **Storage conditions** • Store the drive in a cool, dry place, away from direct sunlight and extreme temperatures. It could be a logic that your drive might have experienced a head crash and/or bad sectors. Therefore, it is a logic that the drive is not stored correctly and could be damaged to your files. If the drive continues to run.

RD DIGITAL

#SuccessStartsHere

Plan of action	**Missing, reformatted or deleted files** Whether it was an accidental deletion or if your files have gone missing. • Stop using the drive immediately to prevent further data loss.
Key contacts	• Jordan Fflubes • Abel Bourne

Revision history

Version	Date	Revision details
1	23/09/2025	n/a

RD DIGITAL